

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. APPLN. NO. 09/787,706

**IN THE SPECIFICATION:**

**Page 5, first full paragraph, delete in its entirety and insert the following new**

**paragraph:**

B<sup>1</sup> In the embodiment shown in Figure 1, it can be seen that case 1 may also be mounted on case 2 by rotating it through 180° in its plane. This would then ~~produce~~produce an incorrect mounting unsuited to a reversible wristwatch. This takes account of the symmetrical arrangement of the horns of first case 1 with respect to the horns of second case 2. In order to avoid this, the symmetry can be broken for example by moving horns 16 and 17 of case 1 towards the exterior of said case 1 and horns 18 and 19 of case 2 towards the inside of said case.

At that moment, case 1 can only be mounted in a single direction on case 2.

**Page 9, fourth full paragraph, delete in its entirety and insert the following new**

**paragraph:**

B<sup>2</sup> It will be noted that the watch shown in Figures 4 to 7 could also include stop members to prevent the movable case moving to the left beyond positions (a) and (e) of Figure 4. For example, ends 142 and 143 of slide-way 140 could be deepened or widened locally so that clicks 144 engage more deeply therein. Another solution consists in providing at least one stop projecting at the left end of each face 117 of bars 110, to act as a stop for the movable case. A stop of this type may also be formed by an element connecting the left ends of the two bars to form a rigid U-shaped frame. Plate ~~122~~112 could then be omitted.

**Page 9, after the last paragraph, insert the following heading:**

**WHAT IS CLAIMED IS:**